

4x16 AWG 600V Flexible Control Cable


Part Number: **3331604xxx**

General Construction: 4 - flexible wires (class 5 per IEC 60228) are cabled together and jacketed.
The cable provides excellent resistance to abrasion, oils and chemicals.

Outer Jacket Material: FR-PU

Outer Diameter: 10 mm nom.

Weight: 137 kg/km



Design & Materials

Conductor Material:	Tinned Copper
Conductor Size:	16 AWG
Conductor Construction:	25x0.25 mm
Insulation Material:	FR-PVC -55°C to 105°C rating
Insulation O.D.:	3.2 mm nom.
Conductor Color Code:	Black, Numbered
Total number of conductors:	4
Outer Jacket Thickness:	1.0 mm nom.
Outer Jacket Color:	See TELDOR Jacket Code
Marking:	Per request

Standards

Applicable Standards:	RoHS 2002/95/EC
Flamability Rating:	IEC 60332-1

Performance

Max. DC Resistance :	15.9 /km@20°C
Voltage Rating:	600 V
Max. Operating Temperature:	+80 °C
Min. Operating Temperature:	-40 °C

Prepared By	Revised By	Version Num	Modified on
Roe Ran	Roe Ran	1.4	02-09-2012

Teldor Cables & Systems Ltd. ("Teldor") reserves the right to make changes to the products described in this catalog without prior notice. Teldor does not assume any liability which may occur due to the use of the products described herein. The information contained in this catalog is the proprietary property of Teldor, and may not be used, reproduced or disclosed to others, in whole or in part, without the written authorization of Teldor.