



Model No.	Capacity	W×D
WS1-6409	9U	600×450

Feature:

- Welded frame, stable structure with precise craftsmanship;
- Single section, compatible with 19" standard equipments;
- Tempered glass front door with over 180 turning degree;
- Removable side panel, easy to install and maintain (lock optional) ;
- Cable entry on the top cover and bottom panel with knock-out plate;
- L-shaped mounting profile, easy to adjustable on the mounting rail ;
- Fan cutout on the top cover, easy to install fan;
- Installing back panel, easy to fix on the wall;
- Various accessories for option;

Standard:

- Comply with ANS/EIA RS-310-D, IEC297-2, DIN41497 PART1, DIN41494 Part 7, GB/T3047.2-92 Standard;

Material:

- SPCC quality cold rolled steel
- Thickness: Mounting profile: 1.5mm; other: 1.2mm;

Loading Capacity:

- Static loading: 60kg

Degree of protection:

- IP20

Surface finish:

- Degreasing, Pickling, Phosphating, Powder Coated

Cabinet Parts:



Installing back panel



Side panel



Mounting angle



Mounting profile




Optional lock




Cable entry



Main structure:



Main Dimension:



Main Component:

No.	Component Name	Quantity	Unit	Material Specification	Surface Finish	Note
1	Top Cover	1	pc	SPCC cold rolled steel T1.2	Powder Coated	--
2	Bottom Panel	1	pc	SPCC cold rolled steel T1.2	Powder Coated	---
3	Frame	2	pc	SPCC cold rolled steel T1.2	Powder Coated	--
4	Mounting profile	4	pc	SPCC cold rolled steel T1.5	Powder Coated	---
5	Side Panel	2	pc	SPCC cold rolled steel T1.2	Powder Coated	Removable steel door
6	Front Door	1	pc	Tempered glass 5mm	Powder Coated	--
7	lock	1	pc	Galvanization	Powder Coated	---
8	M6 B-head screw and M6 square nut	10	pc	Steel	Color Zinc Coated	---
9	Allen Wrench	1	pc	Steel	Black	----
10	Cable entry plate	2	pc	SPCC cold rolled steel T1.2	Powder Coated	--
11	Installing back panel	1	pc	SPCC cold rolled steel T1.2	Powder Coated	--

Optional Accessories:

- Removable side panel can add the lock; Fixed Shelf,
- Various of front door;
- Ornament strip for the glass side
- Brush for cable entry and other design
- Smoked Color glass
- Cantilever

Model Information:

Model No.	Capacity (U)	Width×Depth (mm)	Model No.	Capacity (U)	Width×Depth (mm)
WS1-6404	4	600×450	WS1-6604	4	600×600
WS1-6406	6	600×450	WS1-6606	6	600×600
WS1-6409	9	600×450	WS1-6609	9	600×600
WS1-6412	12	600×450	WS1-6612	12	600×600
WS1-6415	15	600×450	WS1-6615	15	600×600
WS1-6418	18	600×450	WS1-6618	18	600×600
WS1-6422	22	600×450	WS1-6622	22	600×600
WS1-6427	27	600×450	WS1-6627	27	600×600
WS1-6815	15	600×800	WS1-6818	18	600×800

