

Dome Type Heat Shrinkable Fiber Optic Splice Closure (FOSC)

BDH N5



Description:

F2H-FOSC-BDH-N5 Dome Type Heat Shrinkable Fiber Optic Splice Closure (FOSC) is heat shrinkable sealing and suitable for uncut cables.

Specification:

| Model | F2H-FOSC-BDH-N5 |
|------------------------------|--------------------------|
| Туре | Dome type |
| Sealing Structure | Heat shrinkable |
| Number of Inlet/Outlet ports | 5 ports |
| Cable Diameter | 1 port×38mm, 4 port×20mm |
| Maximum Capacity | Bunchy: 144 fibers; |

| | Ribbon:432 fibers |
|--------------------------|----------------------------------------------------------|
| Canacity per Splice Tray | Bunchy: single layer: 12 fibers; dual layers: 24 fibers; |
| Capacity per Splice Tray | Ribbon: standard: 6pcs; max.: 12pcs |
| Quantity of Splice Tray | 6pcs |
| Body Material | PC |
| Sealing Material | Thermoplastic rubber |
| Assembling method | Aerial, direct buried, pipelined, wall mounting, manhole |
| Dimension | 470(H)×210(D)mm |
| Net Weight | 2.5~3.3KG |
| Temperature | -40°C~65°C |



Main Components:

| Item | Name | Usage | Quantity |
|------|--------------------|------------------------------------------|-----------|
| 1 | Housing (Cover) | To protect splices of fiber optic cables | 1pc |
| 2 | Splice Tray | To fix Fiber Splice Protective Sleeves | Max. 6pcs |
| 3 | Fiber Holding Tray | To store loose tube fibers | 1pc |
| 4 | Housing (Base) | To fix internal and external structure | 1pc |
| 5 | Plastic Hoop | To fix Housing Cover and Base | 1pc |
| 6 | Sealing Grommet | To seal Cover and Base | 1 set |

Standard Accessories:

| Item | Name | Usage | Quantity |
|------|-----------------------------------------------------|----------------------------------------|------------------|
| 7 | Heat Shrinkable Protective Tubes and Branching Clip | To seal fiber optic splice closure | As per capacity |
| 8 | Fiber Splice Protective Sleeves | To protect fiber splices | Same as capacity |
| 9 | Nylon Tie | To fix buffer tubes with fibers inside | 8pcs |
| 10 | Grounding Wire | To connect with grounding device | 1рс |
| 11 | Abrasive Cloth | To polish fiber optic cable | 1рс |
| 12 | Labelling Paper | To label fibers | 1 set |
| 13 | Hanging Hoop | To install on wall and pole | 1 set |
| 14 | Heat Shrinkable Fixing Tube (Mass) | To seal fiber cables | optional |
| 15 | Aluminum-foil Paper | To protect cable ports when heated | 1pc |







Buffer Tube

Dessicant

Optional Accessories:

| Item | Name | Usage | Quantity |
|------|------------------|------------------------------------------------|-----------|
| 1 | Valve | To perform pressure and sealing testing | 1pc |
| 2 | Grounding Device | To derive metallic components of fiber cable | 1 set |
| 3 | Buffer Tube | To protect fibers and be fixed on splice trays | specified |
| 4 | Desiccant | To desiccate air in FOSC after sealing | 1 bag |

Ordering Information:

| Brand | F2H |
|-------------------------|----------------------------------------|
| Name | FOSC: Fiber Optic Splice Closure |
| Shape and Sealing | BDH: Dome type heat shrinkable sealing |
| Туре | N |
| Cable Port | 5=5 Ports |
| Fiber Optic Coline Tray | S12: 12-core |
| Fiber Optic Splice Tray | S24: 24-core |
| | 1: 1 tray |
| Number of Splice Trays | 2: 2 trays |
| Number of Splice Hays | 3: 3 trays |
| | |

| | 6: 6 trays |
|------------------|------------------------------|
| Valve | V: Valve included |
| Grounding Device | G: Grounding device included |

For example: F2H-FOSC-BDH-N5S24-4VG